

Auto Tracking Cameras

——JT-HD6oS for Students



Features:

Student tracking camera--JT-HD6oS

- 20X optical zoom, 1/2.8" CMOS, 3.5 Megapixels;
- Auto tracking camera for students;
- **Trigger** Image tracking---when students stand up;
- Patented 2-cam design:
 - 1 for tracking, 1 for panoramic view;
- Outputs: 1/3G-SDI*2:
 - one output is for full image, and the other is for special feature image;
 - 2/RJ45*1:Use to setting digital when connecting with PC;
- Full compatibility with SONY terminal;
- VISCA and PELCO P/D protocol optional.



Shenzhen JinJiuTianShi Industry Co., Limited

Mob.: +86 -18928471586

Email: senior_manager@9ttop.com

Parameters:

Item No.	JT-HD60S
Image Sensor	SONY 1/2.8" Progressive CMOS
Effective Pixels	3.5 Megapixels
Resolution HD	1080p60/50,1080i60/50,1080p30/25,720p60/50
Signal System	PAL/NTSC
Lens	20X optical zoom, f=4.7mm(wide angle end)~94.0mm(far angle end)
Horizontal View Angle	58.7°(W)~3.2°(T)
Focus System	Auto/Manual
Minimum Illumination	0.5 Lux
Exposure Control	Auto/Manual
Shutter Speed	1/25 ~ 1/10,000s
Gain	Auto/Manual
White Balance	Auto/ Indoor/Outdoor/Manual
Image Effect	Full color/black and white/Electronic flip
S/N Ratio	≥50db
Pan	355°(max. speed:80°/s)
Tilt	- 30° to +90° (max. speed: 60°/s)
Preset Position	9 preset positions by IR remote controller, 255 preset positions by PC or keyboard controller
Video Output HD	2 HD-SDI
Other Video Output	WLAN
Control Protocol	SONY VISCA, PELCO P/D
Control Mode	RS-232C, RS-422/485
Power	12V DC(10.8 ~ 13.0V DC)
Power Consumption	Max. 30W(DC 12V)
Operating Temperature	0~40℃
Storage Temperature	-20-60℃
Weight	1710g
Color	Gray
Accessories	DC 12V power adapter, IR Remote, Operation manual, RS-232C Cable, Ceiling bracket
Carton	Each camera in a small carton, then 4 pcs packaged in one large carton
Certificate	ISO/CE/FCC/RoHS
Warranty	3 years